



MULTISPIRAL NO SKIVE



MULTISPIRAL NO SKIVE

The new fittings range is a no-skive solution for high pressure spiral hose.

MAIN FEATURES

- // No-skive
- // Range: from 3/4 inch to 2 inch sizes
- // Working pressures: up to 6000 psi (420 bar)
- // Main applications: construction equipment, agricultural machines, mining
- // Suitable for: aftermarket and maintenance activities, on-site repairs especially

ADVANTAGES

- // No need of skiving equipment, no odor and dust (consequence of the hose cover removal)
- // Easy and fast hose assembly operations



NO-SKIVE DESIGN

The Multispiral no-skive is the alternative to the Interlock range, much easier to assemble and still with a high performance.



// NO SKIVE FERRULE FOR MULTISPIRAL FITTINGS

Hose	Table n°	-06 DN 10 3/8"	-08 DN 12 1/2"	-10 DN 16 5/8"	-12 DN 19 3/4"	-16 DN 25 1"	-20 DN 32 1 1/4"	-24 DN 38 1 1/2"	-32 DN 51 2"	-40 DN 63 2 1/2"	-48 DN 76 3"
ALFABIOTECH 4000 MINETUFF	275							H1300NS4	H1300NS4		
ALFABIOTECH 5000 MINETUFF - 4S	276				H1300NS4	H1300NS4	H1300NS4				
ALFABIOTECH 5000 MINETUFF - 6S	280							H1300NS6	H1300NS6		
ALFABIOTECH 5000 PLUS MINETUFF	277				H1300NS4	H1300NS4					
ALFABIOTECH 6000 MINETUFF - 4S	278				H1300NS4	H1300NS4					
ALFABIOTECH 6000 MINETUFF - 6S	282						H1300NS6				